



ATF Dexron III (Red)

Product Code: SCDEX3 - Revision: 20181122

Product Description

Formulated from highly refined base stocks and an additive package designed to impart the requirements of oxidation stability and anti-wear characteristics. Benefits of longer life and use in the more severe conditions of service demanded by the test requirements of this up to date performance fluid. An automatic transmission fluid that demonstrates excellent frictional stability and EP characteristics ensuring confidence of operation in passenger cars and heavy duty equipment throughout its service life.

Benefits

- Constant frictional performance.
- Oxidation stability.
- High temperature operation stability.
- Wear protection.
- Low temperature fluidity.
- Seal compatibility.
- Smooth operation of power transmission and power steering systems.

Applications

Recommended for use in automatic transmissions of passenger cars, trucks and buses where Dexron IID, Dexron IIE, Dexron III and Ford Mercon fluids are specified, also in Mercedes Benz passenger car manual gearboxes and power shift transmissions.

The use of this product should be avoided where Ford Type G ATF fluid is specified.

Typical Test Data

Density @ 15°C	-	0.84
Flash Point (°C)	-	>180
Kinematic Viscosity @ 100°C (cSt)	-	7.5
Kinematic Viscosity @ 40°C (cSt)	-	37
Pour Point (°C)	-	<-40
Viscosity Index	-	176

Product Profile

Allison	C4, TES 389
Caterpillar	TO-2
Ford	Mercon
GM	Dexron IIIH
MAN	339 Z1, V1, Z2, V2
MB	236.1, 236.5, 236.6, 236.7, 236.9
Voith	55.6335, 55.6636
Volvo	97340, 97341
ZF-TE-ML	02F, 03D, 04D, 09, 11A/B, 14A/B, 16L, 17C